

## TGV-2600





BEST PRODUCTS
BEST LOCAL SUPPORT

## FOR MORE INFORMATION CALL 1-800-323-1604

OR YOUR LOCAL DEALER

www.sewerequipment.com

Outside USA: 847-729-3316 E-Mail: sales@sewerequipment.com The TGV-2600 trailer mounted combination unit combines system to clean and remove debris from sanitary and storm soil using the hydro—excavation method. Other applicatio telecommunications vaults, skimming grease from disposal sewer cleaning and vacuum conveyance work.

Quick Flange Locks allow for the quick disconnection and replacement of vacuum tubes to accommodate the depth or distance of the debris to be removed.

Rear Door features mechanical over hydraulic locks for

positive sealing

Liquid discharge system will pump off excess liquid. This limits the amount of liquid in the debris tank leaving more room for solid debris

<u>Convenient Tube</u> <u>Storage</u> makes it easy to start a job fast.

Rear Mounted Hose Reel the rear mounted position of the hose reel allows you to clean and vac at the same time while being safely out of the way of traffic. The reel can hold up to 600' of 3/4" sewer hose.

<u>Hydraulic Boom</u> Extension gives the boom an extra 60" of reach for getting to those difficult off road jobs. 600 Gallon Debris Tank (3 cubic yard) gives you more than ample storage for most jobs.

High Pressure Water
The water pump will
gallons per minute a
for all of you sewer of
and hydro excavation



# safety and compact size to provide the most effective sewer lines. It also allows you to safely dig and remove ns include the cleaning of catch basins, lift stations, digesters, sand, gravel, camp latrines, and all general

deliver 40 t 2000 PSI leaning n needs. Industrial Worm Gear Drive is standard on the TGV-2600. The worm drive provides hydraulic rotation through a 320° arc making placement of the flexible vacuum hose easy and accurate.

Power Plant - The TGV-2600 is powered by a powerful diesel engine coupled to a multi drive gear box and independent hydraulic motors to efficiently run both the positive displacement blower and the high pressure water pump.

1,400 CFM Positive
Displacement Blower is standard on the TGV-2600 combination unit.





Watertight Controls are contained in a weatherproof NEMA 4 control box located convieniently at the rear hose reel work station.

Wireless Remote gives the freedom to work independently without the worry of tangled cords.

Information may vary. All specifications listed are based on the latest product information available at the time of publication. The right is reserved to make changes at any time without notice. Some items shown may be optional.



## PRODUCTS

#### TRUCK JETS



800-HPRTV



800-CR



800-HPR



800-H

#### TRAILER JETS



747-FR2000TV



747-FR2000



747-300R



747-PR2000

### OTHER PRODUCTS



**BUCKET MACHINES** 



RODDERS



**EASEMENT MACHINES** 



VACS



BEST PRODUCTS
BEST LOCAL SUPPORT

FOR MORE INFORMATION CALL 1-800-323-1604

OR YOUR LOCAL DEALER

www.sewerequipment.com

Outside USA: 847-729-3316 E-Mail: sales@sewerequipment.com